

## 10.1" Mobile POS System MP-1311



### Features

- The tablet can comply with common form
- Less customization and easier future maintenance
- Its compact footprint takes space saving to the extremes and creates a clean, cable-free and concise environment
- Enhance the checkout experience that can move customers quickly through the line
- Sleek, modern and adaptable design
- Module architecture for efficient chassis integration
- Wrist straps are available for true product mobility and security
- Rich External Devices and Cradle supported

### Color Variation



## Specifications

Model	MP-1311-A	MP-1311-B	MP-1311-C	MP-1311-E	MP-1311-F
<b>Main System</b>					
Processor	Intel Atom® x5-Z8350 Quad Core 1.44GHz, up to 1.92GHz				
Display	10.1-inch IPS, 1280 x 800, 300nits				
Touch Panel	True-Flat Projected-Capacitive Multi Touch (PCAP)				
Memory	4GB DDR3L 1600MHz				
Storage	64GB eMMC				
Micro-SD Slot	Up to 128GB				
Communication	Wi-Fi IEEE 802.11 b/g/n, Bluetooth 4.0 and GPS				
Webcam	2M Front Camera (FF) and 5M Rear Camera (AF)				
Speaker	2 x 0.8W Speakers				
Sensor	Light Sensor, G Sensor and Gyroscope				
<b>I/O Interface</b>					
USB	1 x USB 3.0 Type A				
Po-go Pin	1 x Pogo Pin (for charging and data transmission)				
<b>Peripherals</b>					
External Modules	MSR	MSR	MSR	N/A	MSR
	2D Barcode Scanner	2D Barcode Scanner	2D Barcode Scanner	2D Barcode Scanner	N/A
	Finger Print	N/A	N/A	N/A	N/A
	N/A	NFC	N/A	N/A	N/A
<b>Power Management</b>					
Internal Battery	Lithium Polymer Battery 4800mAh				
Power Adapter	5V@3A 15W AC Power Adapter (option)				
<b>Mechanical &amp; Environmental</b>					
Dimension	Main Tablet : 310 (W) x 187.2 (H) x 25.9 (D) mm				
	Dock Station : 220.5 (W) x 160.8 (H) x 125.8 (D) mm				
Weight	Main Tablet : 0.95kg (w/o accessories)				
	Dock Station : 1.23kg (w/o power adapter)				
Operation System	Windows 10 IoT Ent LTSPB Entry EPKEA				
Certification	CE / FCC Class B				
Operation Condition	0°C to +40°C / 10 to 85% without condensation				
Charging Condition	0°C to +40°C / 10 to 85% without condensation				
Storage Condition	-10°C to +50°C / 10 to 85% without condensation				



Optional Accessories	
<b>Dock Station (CB-1300-C)</b>	2 x USB 2.0, 1 x COM (DB9), 1 x LAN, 1 x DC-in and 1 x Pogo Pin (for charging and data transmission) 12V@2A 24W AC Power Adapter
<b>Dock Station (CB-1300-D)</b>	3 x USB, 2 x COM (RJ45, w/0/5V/12V), 1 x LAN, 1 x DC-in and 1 x Pogo Pin (for charging and data transmission) 12V@3A 36W AC Power Adapter
<b>Charging Cradle (CB-1300-E)</b>	I/O Connectors : 1 x DC-in and 1 x Pogo Pin (for charging) 12V@2A 24W AC Power Adapter
<b>Tablet Power Adapter</b>	5V@3A 15W AC Power Adapter
<b>Cable</b>	RJ45 to DB9 Cable (50cm)
<b>Hand Strap</b>	Design to securely hold the MP-1311-X Series Tablet

